

Precision High-Power Bulk Metal[®] Foil Resistors, and Thick Film Power Resistors

Product Overview



ES COMPONENTS
108 PRATTS JUNCTION ROAD
STERLING, MA 01564

PHONE: (978)422-7641

FAX: (978)422-0011

www.escomponents.com

<http://www.escomponents.com/accelerated-resistor-sample-request>



powertron.de

A PART OF
VISHAY FOIL RESISTORS



Precision High-Power Bulk Metal® Foil Resistors, and Thick Film Power Resistors



Powertron GmbH, a brand of Vishay Precision Group, Inc. (VPG) and part of VPG's Vishay Foil Resistors product line, is dedicated to the development, manufacturing, and marketing of high-precision foil, current sense, and thick film resistors for use in diverse applications. Powertron offers a full complement of resistors for accurate, precise, and high-power circuits, with customization capabilities supporting virtually any package type.

Powertron focuses on delivering solutions with the best combination of power ratings, TCR, and resistance ranges. Our foil resistor products include devices built on CuNiMn Bulk Metal® Foil for low-ohm, high-precision applications, with TCR down to 5 ppm and long-term stability of 0.1%; as well as NiCr foil for even higher levels of stability, with TCR of 1 ppm and long-term stability of 0.01%. A supplemental thick film product line is also available in a wide range of packages. Powertron produces thick film power resistors in standard sizes, in addition to custom solutions with "as-required" resistor values.

Made in Germany, with local customer service and technical support providing high flexibility, our products are used throughout the world in high-precision medical, aerospace, military, and industrial applications.

Powertron in Action

Medical

Accurate and stable instrumentation in the medical field requires the ability to detect very small signals without producing false readings. For the resistors surrounding the operational amplifier and anywhere else they are needed in medical applications, the preferred choice of device is Powertron foil.

End Product

Hemodialysis Equipment (Reference resistor for high-accuracy temperature measurement)

Customer Requirements

- High-precision resistance values
- High stability over time (0.01% for 2000 h)
- Low TCR in the range of -55°C to +125°C
- Customized resistance values from 90R0 to 210R0

Powertron Foil Solution: **USR 2-0710**

High-precision, highly reliable resistor

Precise measurement with following parameters:

- Customized resistance values available
- TCR down to 1 ppm
- Stability of 0.01% over time



Industrial

Industrial systems sometimes favor price over quality when it comes to electronic components, but when all factors are taken into consideration, quality resistors turn out to be the least expensive solution. In the long run, a reliable and stable resistor costs less than one that must be replaced or which requires additional circuitry to compensate for lack of precision. Factor in warranty repair expense, downtime in the hands of the customer, and transportation costs for repairs, and the “savings” from using second-best resistors quickly disappear. Even when an assumed or measured returns rate is applied, Powertron foil current sense resistors turn out to be the most economical solution.

End Product

Test instruments for high-voltage equipment

Customer Requirements

- High-precision current measurement
- High stability over time (0.1% for 1000 h)
- Low TCR in the range of 10°C to 80°C
- Low resistance value (0.005 Ω to 0.010 Ω)
- High power rating with up to 40 W
- Must endure short-time overload without changing parameters

Powertron Foil Solution: **FHR 4-3825**

Low-ohmic, high-precision, and high-power current sense resistor

Precise measurement with following parameters:

- Resistance values starting from 0.001 Ω
- Power rating up to 50 W
- TCR down to 15 ppm
- 4-terminal Kelvin connection for high-precision measurement



Precision Instrumentation

Whether they are used in the guidance system of a cruise missile, high-precision power supplies, or in precision measurement equipment, Powertron foil resistors are consistently the best choice for precision instrumentation because of their initial accuracy and long term stability.

End Product

Labor current supply for 1- and 3-phase electrical networks

Customer Requirements

- High-precision current measurement for outgoing current quality control
- High stability over time (0.1% for 1000 h)
- Low TCR in the range of 20°C to 60°C
- Low resistance values (0.001 Ω to 0.002 Ω)
- High power rating with up to 60 W
- High-current applications up to 165 A

Powertron Foil Solution: **FPR 4-T227**

Low-ohmic, high-precision, and high power current sense resistor

Precise current measurement with the following parameters:

- Resistance values starting from 0.001 Ω
- Power rating up to 60 W
- TCR down to 15 ppm
- 4-terminal Kelvin connection for high precision measurement
- Available with special high current terminals on for high-precision measurement



Power Distribution

Electrical power is becoming more expensive and the need to more precisely control its distribution will be a key factor in the future. For such applications it is mandatory to use highly reliable electronic components, as these systems have a long lifetime in the field. Measuring current is one of their most important features, so stable and reliable resistors are required. Such resistor provide accurate measurements over a long time, while minimizing repair expenses and downtime. Powertron Bulk Metal Foil current sense resistors are the most economical solution.

End Product

Current measurement in bus-bar systems

Customer Requirements


- Low resistance value (<0.0005 Ω)
- High stability over time
- Low TCR in the range of -20°C to $+75^{\circ}\text{C}$
- Customized resistance design

Powertron Foil Solution: **Special Products**

High-precision, reliable resistor

Precise measurement with following parameters:

- Customized resistance values below 1 m Ω
- TCR down to 20 ppm
- Stability of 0.1% over time



Aerospace

The demands of the aerospace segment differ from commercial segments in one major aspect: ongoing reliability. In some cases there is only one chance to complete the mission, and the system cannot be brought back into the shop for repairs. Some systems must transit in deep space for 10 years or more before being activated. Every component must activate when required and perform flawlessly to the end of the mission. This is why Powertron resistors, with their long-term consistency and reliability, are the only choice for aerospace applications.

End Product

Current measurement in satellites

Customer Requirements

- High precision resistance value
- High stability over time
- Low TCR in the range of -20°C to $+85^{\circ}\text{C}$
- Customized resistance values

Powertron Foil Solution: **FHR 4-2321**

High-precision, reliable resistor

Precise measurement with following parameters:

- Customized resistance values from 1 m Ω to 50 Ω
- TCR down to 15 ppm
- Stability of 0.1% over time



Audio

In audio systems, “high end” means faithful reproduction of the original signal and the absence of noise insertion by the electronic components — particularly the resistors. The audio discrimination level is sometimes beyond the instrument’s measuring capability, but is nonetheless aurally detectable. Vishay Foil Resistors devices offer the lowest noise available for such resistors, and are essential components of any high-end audio system.

End Product

Loudspeaker systems

Customer Requirements

- Customized resistance values
- High stability over time
- Low TCR in the range of -20°C to $+60^{\circ}\text{C}$
- Customized resistance design

Powertron Foil Solution: **FPR 2-T218**

High-precision, reliable resistor

Precise resistance with following parameters:

- Customized resistance values from $0.100\ \Omega$ to $20\ \Omega$
- TCR down to 25 ppm
- Stability of 0.1% over time



Aviation

The electronics used in commercial avionics are exposed to dramatic temperature excursions, shock and vibration, moisture, and the test of time. In engine, cabin, and flight control applications, resistors need to maintain their values despite all of these factors.

End Product

Used in multiple electronic systems, such as temperature control

Customer Requirements

- High-precision resistance values
- High stability over time
- Customized resistance values

Powertron Foil Solution: **KHR 2-T227**

High-precision, reliable resistor




Precise power resistor with following parameters:

- Customized resistance values from $1\ \Omega$ to $50\ \text{k}\Omega$
- Power rating up to 200 W
- Standard TO-227 / 238 housing



Precision High-Power Bulk Metal® Foil Resistors, and Thick Film Power Resistors

Powertron's high-precision power CuNiMn current sense resistors offer a wide range of capabilities for different applications, and are available with any resistance value requested by the customer.

Product	Description
	<p>FPR 2-1617 FPR 2-1623 FPR 2-2614</p> <p>Resistance values from 0.01 Ω to 100 Ω Power rating to 2 W Resistance tolerances to ±0.1% TCR to ±50 ppm/K Load stability to 0.1%</p>
	<p>FPR 4-3316</p> <p>Resistance values from 0.001 Ω to 100 Ω Power rating to 2 W Resistance tolerances to ±0.1% TCR to ±25 ppm/K Load stability to 0.1%</p>
	<p>PCS201 PCS202</p> <p>Resistances from 0.001 Ω to 10 Ω Power rating to 2 W Resistance tolerances to ±0.1% TCR to ±15 ppm/K Load stability to 0.1%</p>
	<p>FPR 4-6025</p> <p>Resistance values from 0.100 Ω to 10 Ω Power rating to 4 W Resistance tolerances to ±0.2% TCR to ±15 ppm/K Other dimensions upon request</p>
	<p>FPS 2-T220</p> <p>Resistance values from 0.002 Ω to 10 Ω Power rating to 15 W Resistance tolerances to ±0.5% TCR to ±50 ppm/K Load stability to 0.1% SMD D2Pak</p>
	<p>FPS 4-T220</p> <p>Resistance values from 0.002 Ω to 10 Ω Power rating to 15 W Resistance tolerances to ±0.1% TCR to ±25 ppm/K Load stability to 0.1% SMD D2Pak</p>
	<p>FPR 2-T220 FPR 2-T221</p> <p>Resistance values from 0.002 Ω to 10 Ω Power rating to 15 W Resistance tolerances to ±0.1% TCR to ±50 ppm/K Load stability to 0.1% TO-220 housing</p>
	<p>FPR 4-T220 FPR 4-T221</p> <p>Resistance values from 0.002 Ω to 10 Ω Power rating to 15 W Resistance tolerances to ±0.1% TCR to ±25 ppm/K Load stability to 0.1% TO-220 housing</p>
	<p>FPR 2-T218</p> <p>Resistance values from 0.002 Ω to 20 Ω Power rating to 30 W Resistance tolerances to ±0.25% TCR to ±50 ppm/K Load stability to 0.1% TO-218 (TO-247) housing</p>

Powertron's high-precision power CuNiMn current sense resistors offer a wide range of capabilities for different applications, and are available with any resistance value requested by the customer.

Product	Description
	<p>FHR 2-3025 FHR 2-3818</p> <p>Resistance values from 0.01 Ω to 100 Ω Power rating to 40 W Resistance tolerances to ±0.25% TCR to ±50 ppm/K Very low inductance Stability to 0.1%</p>
	<p>PCS301 PCS302</p> <p>Resistance values from 0.001 Ω to 50 Ω Power rating to 40 W Resistance tolerances to ±0.1% TCR to ±15 ppm/K Very low inductance Load stability to 0.1%</p>
	<p>FHR 4-2321</p> <p>Resistance values from 0.001 Ω to 50 Ω Power rating to 40 W Resistance tolerances to ±0.1% TCR to ±25 ppm/K Very low inductance Load stability to 0.1%</p>
	<p>FHR 4-3825 FHR 4-4618</p> <p>Resistance values from 0.001 Ω to 100 Ω Power rating to 50 W Resistance tolerances to ±0.1% TCR to ±25 ppm/K Very low inductance Load stability to 0.1%</p>
	<p>FPR 2-T227 FNR 2-T227</p> <p>Resistance values from 0.001 Ω to 100 Ω Power rating to 80 W Resistance tolerances to ±0.1% TCR to ±50 ppm/K Load stability to 0.1%</p>
	<p>FPR 4-T227 FNR 4-T227</p> <p>Resistance values from 0.001 Ω to 100 Ω Power rating to 80 W Resistance tolerances to ±0.1% TCR to ±15 ppm/K Load stability to 0.1%</p>
	<p>FHR 2-8065 FHR 2-80110 FHR 2-80216 FHR 2-80320 FHR 2-80370</p> <p>Resistance values from 0.001 Ω to 500 Ω Power rating to 2500 W Resistance tolerances to ±0.1% TCR to ±50 ppm/K Load stability to 0.1% Very low inductance (<50 nH)</p>
	<p>FHR 4-8065 FHR 4-80110 FHR 4-80216 FHR 4-80320 FHR 4-80370</p> <p>Resistance values from 0.001 Ω to 500 Ω Power rating to 2500 W Resistance tolerances to ±0.1% TCR to ±25 ppm/K Load stability to 0.1% Very low inductance (<50 nH)</p>
	<p>FPN Net Works FHN Net Works</p> <p>Resistor values over four decades 0.010 Ω to 90 Ω Kelvin connection Resistance tolerances to ±0.1% TCR to ±15 ppm/K Load stability to 0.1%</p>

Precision High-Power Bulk Metal® Foil Resistors, and Thick Film Power Resistors

Powertron's high-precision power CuMnSn current sense resistors offer the best available TCR for high-power current measurement. The devices are available as free-standing resistors, with a metal plate for heat sink mounting, as well as surface-mount applications.










Product	Description
	<p>SPS 4-T220</p> <p>Resistance values from 0.01 Ω to 10 Ω Power rating to 15 W Resistance tolerances to ±0.1% TCR to ±5 ppm/K Load stability to 0.1% SMD D2Pak</p>
	<p>SPR 4-T220 SPR 4-T221</p> <p>Resistance values from 0.005 Ω to 10 Ω Power rating to 15 W Resistance tolerances to ±0.1% TCR to ±2 ppm/K Load stability to 0.1% TO-220 Housing</p>
	<p>SHR 4-2321</p> <p>Resistance values from 0.005 Ω to 20 Ω Power rating to 40 W Resistance tolerances to ±0.1% TCR to ±2 ppm/K Load stability to 0.1% Very low inductance</p>
	<p>SHR 4-4618</p> <p>Resistance values from 0.005 Ω to 50 Ω Power rating to 50 W Resistance tolerances to ±0.1% TCR to ±2 ppm/K Load stability to 0.1% Very low inductance</p>
	<p>SHR 4-3825 SHR 4-3825H</p> <p>Resistance values from 0.005 Ω to 50 Ω Power rating to 50 W Resistance tolerances to ±0.1% TCR to ±2 ppm/K Load stability to 0.1% Very low inductance</p>
	<p>SPR 4-T227 SNR 4-T227</p> <p>Resistance values from 0.002 Ω to 20 Ω Power rating to 80 W Resistance tolerances to ±0.1% TCR to ±2 ppm/K Load stability to 0.1% Very low inductance</p>
	<p>SHR 4-8065 SHR 4-80110 SHR 4-80216 SHR 4-80320 SHR 4-80370</p> <p>Resistance values from 0.005 Ω to 300 Ω Power rating to 2500 W Resistance tolerances to ±0.1% TCR to ±2 ppm/K Load stability to 0.1% Very low inductance</p>
	<p>SPN Networks SHN Networks</p> <p>Resistor values over four decades 0.010 Ω to 90 Ω Kelvin connection Resistance tolerances to ±0.1% TCR to ±2 ppm/K Load stability to 0.1%</p>

Powertron's special resistors are designed upon customer request and can vary in dimensions, resistive elements and technologies used, contacts, and further parameters as needed by the customer.

Product	Description
	<p>SHR 4-2820</p> <ul style="list-style-type: none"> • Resistance values from 0.001 Ω to 0.01 Ω • Power rating to 10 W • Resistance tolerances to $\pm 1\%$ • TCR to ± 70 ppm/K • Load stability to 0.5%
	<p>FHR 4-4026H</p> <ul style="list-style-type: none"> • Resistance values from 0.0005 Ω to 10 Ω • Power rating to 15 W • Resistance tolerances to $\pm 0.25\%$ • TCR to ± 20 ppm/K
	<p>CAL 4-40100</p> <ul style="list-style-type: none"> • Calibration resistor • Resistance values from 0.0001 Ω to 10 kΩ • Current to 60 A • Resistance tolerances to $\pm 0.02\%$ • TCR to ± 10 ppm/K
	<p>FHR 4-2036</p> <ul style="list-style-type: none"> • Resistance values upon customer request • Power rating to 5 W • Resistance tolerances to $\pm 0.2\%$ • TCR to ± 15 ppm/K • 350 J pulse capabilities
	<p>UHR 4-5020D</p> <ul style="list-style-type: none"> • Resistance values from 1 Ω to 40 Ω • Power rating to 8 W • Resistance tolerances to $\pm 0.1\%$ • TCR to ± 5 ppm/K • Load stability to 0.1% • Pulse energy up to 1000 J/1 s
	<p>WPR 2-TO5</p> <ul style="list-style-type: none"> • Resistance values from 50 Ω to 600 kΩ • Resistance tolerances to $\pm 0.01\%$ • TCR to ± 5 ppm/K • Load stability to 0.1% • Hermetically sealed
	<p>High Power Resistor Bank</p> <ul style="list-style-type: none"> • Power resistors mounted on heat sink • Resistance values from 0.001 Ω to 500 Ω • Power rating to 2500 W • Resistance tolerances to $\pm 0.1\%$ • TCR to ± 2 ppm/K • Load stability to 0.1%

Precision High-Power Bulk Metal® Foil Resistors, and Thick Film Power Resistors




Powertron's NiCr foil resistors are specially designed for high-power applications with power dissipation up to 50 W. These products also offer the best performance for TCR, load stability, and tolerance.

Product	Description
	<p>USR 2-0808</p> <p>Resistance values from 1 Ω to 150 kΩ Power rating to 0.6 W Resistance tolerances to $\pm 0.005\%$ TCR to ± 1 ppm/K Load stability to 0.01%</p>
	<p>USR 2-0710 UNR 2-0710</p> <p>Resistance values from 1 Ω to 150 kΩ Power rating to 0.6 W Resistance tolerances to $\pm 0.005\%$ TCR to ± 1 ppm/K Load stability to 0.01%</p>
	<p>USS 2-T220 UNS 2-T220</p> <p>Resistance values from 0.5 Ω to 150 kΩ Power rating to 15 W Resistance tolerances to $\pm 0.01\%$ TCR to ± 3 ppm/K Load stability to 0.01% SMD D2Pak</p>
	<p>USS 4-T220 UNS 4-T220</p> <p>Resistance values from 0.2 Ω to 80 Ω Power rating to 15 W Resistance tolerances to $\pm 0.01\%$ TCR to ± 1 ppm/K Load stability to 0.01%</p>
	<p>USR 2-T220 USR 2-T221 UNR 2-T220 UNR 2-T221</p> <p>Resistance values from 0.5 Ω to 150 kΩ Power rating to 10 W Resistance tolerances to $\pm 0.01\%$ TCR to ± 3 ppm/K Load stability to 0.01% TO-220 housing</p>
	<p>USR 4-T220 USR 4-T221 UNR 4-T220 UNR 4-T221</p> <p>Resistance values from 0.2 Ω to 80 Ω Power rating to 15 W Resistance tolerances to $\pm 0.01\%$ TCR to ± 1 ppm/K Load stability to 0.01%</p>
	<p>USR 4-3425 UNR 4-3425</p> <p>Resistance values from 0.05 Ω to 500 Ω Power rating to 50 W Resistance tolerances to $\pm 0.01\%$ TCR to ± 1 ppm/K Load stability to 0.01%</p>
	<p>PCS331 PCS332</p> <p>Resistance values from 0.05 Ω to 500 Ω Power rating to 50 W Resistance tolerances to $\pm 0.01\%$ TCR to ± 1 ppm/K Load stability to 0.01%</p>
	<p>USR 4-4020 UNR 4-4020</p> <p>Resistance values from 0.05 Ω to 100 Ω Power rating to 50 W Resistance tolerances to $\pm 0.01\%$ TCR to ± 1 ppm/K Load stability to 0.01%</p>

Powertron thick film resistors are completing the power line of Powertron Foil resistors. They are available in standard housings and will be delivered with any resistance value.

Product	Description
	<p>NPS 2-T126</p> <p>Resistance values from 0.025 Ω to 10 kΩ Power rating to 25 W Resistance tolerances to ±1% TCR to ±100 ppm/K Load stability to 0.5% TO-126 housing (D-Pak) Solder reflow secure at 260°C / 20s</p>
	<p>NPS 2-T220 NHS 2-T220</p> <p>Resistance values from 0.02 Ω to 100 kΩ Power rating to 50 W Resistance tolerances to ±1% TCR to ±50 ppm/K Load stability to 0.5% TO-220 SMD housing</p>
	<p>NPR 2-T220 NHR 2-T221</p> <p>Resistance values from 0.02 Ω to 100 kΩ Power rating to 50 W Resistance tolerances to ±1% TCR to ±50 ppm/K Load stability to 0.5% TO-220 housing</p>
	<p>KPR 2-T218 KHR 2-T218</p> <p>Resistance values from 0.05 Ω to 100 kΩ Power rating to 100 W Resistance tolerances to ±1% TCR to ±100 ppm/K Load stability to 1% TO-218 (TO-247) housing</p>
	<p>KPR 2-T227 KHR 2-T227</p> <p>Resistance values from 0.05 Ω to 5 MΩ Power rating to 200 W Resistance tolerances to ±1% TCR to ±50 ppm/K TO-227 (TO-238) housing</p>
	<p>KPR 4-T227 KHR 4-T227</p> <p>Resistance values from 0.05 Ω to 5 MΩ Power rating to 200 W Resistance tolerances to ±1% TCR to ±50 ppm/K TO-227 (TO-238) housing</p>
	<p>KPN 2-T227 KHN 2-T227</p> <p>Resistance values from 0.05 Ω to 5 MΩ Power rating to 200 W Resistance tolerances to ±1% TCR to ±50 ppm/K TO-227 (TO-238) housing</p>

A PART OF
VISHAY FOIL RESISTORS



Resistor Sample Request

Expedited!

<http://www.escomponents.com/expedited-resistor-sample-request>



ES COMPONENTS
108 PRATTS JUNCTION
ROAD STERLING, MA 01564
PHONE: (978)422-7641
FAX: (978)422-0011
www.escomponents.com



DISCLAIMER: ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE. Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein. VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.** Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com. No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG. The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.